


Applique Link

 Collection: test en

Simple and minimalist, the Link collection frames the light. Depending on the position of the light, the refined line can be fitted vertically or horizontally.

Link can be placed both horizontally or vertically on the wall. The wall light is adjustable in 2 ways. The front LED bar can be spinned around to diffuse the light in any direction and the rectangular frame can be flipped up and down when the light is positioned horizontally, and side to side when positioned vertically. Custom dimensions available upon request.

Types of design



Link wall light

Finishes



Satin
Copper



Polished
Copper



Satin
Brass



Polished
Brass



Satin
Graphite

Polished
Graphite



Satin
Nickel

Polished
Nickel

Material

Solid Brass

Polycarbonate diffuser

Technical specifications

France et autres

Link 985mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	860lm	2700°K	10W	Int. power supply 24V included	Yes - Phase cut

Link 725mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	620lm	2700°K	8W	Int. power supply 24V included	Yes - Phase cut

Link 525mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	430lm	2700°K	6W	Int. power supply 24V included	Yes - Phase cut

Link 375mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	290lm	2700°K	5W	Int. power supply 24V included	Yes - Phase cut

Link 275mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	290lm	2700°K	4W	Int. power supply 24V included	Yes - Phase cut

USA & Canada



Link 985mm



Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	860lm	2700°k	10W	Int. power supply 24V incl	No

Link 725mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	620lm	2700°k	8W	Int. power supply 24V incl	No

Link 525mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	430lm	2700°k	6W	Int. power supply 24V incl	No

Link 375mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	290lm	2700°k	5W	Int. power supply 24V incl	No

Link 275mm

Lamping	Luminous flux	Color temperature	Power	Int. power supply	Dimmable
Integrated LED	290lm	2700°k	4W	Int. power supply 24V incl	No